

MATERIAL SAFETY DATA SHEET

PRODUCT IDENTIFICATION

PRODUCT NAME: ELECTRIC MOTOR CLEANER PART #: N4835

(NFPA RATINGS) HEALTH: 2 FIRE: 0 **REACTIVITY:** 0 HMIS PROTECTIVE EQUIPMENT: X See your supervisor

PRODUCT INFORMATION (800) 262-0012 TRANSPORTATION EMERGENCY CHEMTREC (800) 424-9300

MEDICAL EMERGENCY (856) 455-4555 **DISTRIBUTOR / MANUFACTURER** NATIONAL REFRIGERANTS, INC. 661 KENYON AVE. ROSENHAYN, NJ

HAZARDOUS INGREDIENTS

50

25 1000

5000

OSHA Hazardous Components (29 CFR 1910.1200)

Trichloroethylene (79-01-6) Perchloroethylene (127-18-4) Acetone (67-64-1) Carbon Dioxide (124-38-9)

EXPOSURE LIMITS: 8 HR. TWA OSHA PEL ACGIH TLV

50
25
750
5000

HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: INHALATION ; SKIN ABSORPTION

POTENTIAL HEALTH EFFECTS:

INHALATION: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.

EYE CONTACT: Irritation. SKIN CONTACT: Irritation due to defatting of skin. **INGESTION:** Possible chemical pneumonitis if aspirated into lungs. Nausea.

CHRONIC Effects: (Effects due to excessive exposure to the raw materials of this mixture) May cause liver abnormalities, kidney, spleen, lung or brain damage, cardiac abnormalities. Perchloroethylene has been shown to increase the rate of spontaneously ocurring malignant tumors in certain laboratory rats and mice.

Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin or upper respiratory conditions..

WARNING: This product contains a chemical or chemicals known to the State of California to cause cancer.

CARCINOGEN REFERENCE SOURCE:

TRICHLORETHYLENE	b
PERCHLOROETHYLENE	a,b
ACETONE	d
CARBON DIOXIDE	d

Chemical listed as carcinogen or potential carcingen. (a) NTP (b) IARC Monograph (c) OSHA (d) Not Listed (e) Animal data only.



MATERIAL SAFETY DATA SHEET

FIRST AID MEASURES

INHALATION: Remove to fresh air. Resuscitate if necessary. Get medical attention.

EYE CONTACT: Flush with water for 15 minutes. If irritated, seek medical attention.

SKIN CONTACT: Wash with soap and water. If irritated, seek medical attention.

INGESTION: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

FIRE AND EXPLOSION HAZARD DATA

 FLAMMABILITY as per USA FLAME PROTECTION TEST (Aerosols): Non-flammable

 FLASHPOINT AND METHOD USED (non-aerosols): N/A

 FLAMMABILITY LIMITS IN AIR BY % IN VOLUME: % LEL: N/E

 AUTOIGNITION TEMPERATURE: N/E

 UNUSUAL FIRE & EXPLOSION HAZARDS: Do not expose to temperature above 130°F or the container may rupture.

 SPECIAL FIRE FIGHTING INSTRUCTIONS: Self contained breathing apparatus.

 EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.

PRECAUTIONS FOR SAFE HANDLING & USE

Steps to be taken if Material is Spilled or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. Allow to evaoprate if small spill. DO NOT FLUSH TO SEWER.

WASTE DISPOSAL METHODS: Aerosol cans, when vented to atmospheric pressure through normal use, pose no disposal hazard.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not puncture or incinerate containers. Do not store at temperatures above 130° F.

OTHER PRECAUTIONS AND OR SPECIAL HAZARDS: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid inhalation of vapors.

CONTROL AND PROTECTIVE MEASURES

RESPITORY PROTECTION (specify type): If vapor concentration exceeds TLV, use respirator approved by US Bureau of Mines for organic vapors.

PROTECTIVE GLOVES: Neoprene gloves recommended.

EYE PROTECTION: Safety glasses recommended.

VENTILATION REQUIREMENTS: Adequate ventilation to keep vapor concentration below TLV.

OTHER PROTECTIVE CLOTHING AND EQUIPMENT: None.

HYGIENIC WORK PRACTICES: Wash with soap and water before handling food. Remove contaminated clothing.

PHYSICAL AND CHEMICAL CHARACTERISTICS

VAPOR PRESSURE: psig @ 70°f (aerosols): 85-100 SPECIFIC GRAVITY: (H20 = 1) Concentrate only = 1.60 EVAPORATION RATE (N-BUTYL ACETATE=1): 2.1 (concentrate only) APPEARANCE & ODOR: Clear, colorless spray with chlorinated solvent odor. VAPOR PRESSURE: (non-aerosols)(mm Hg and temperature): N/A

VAPOR DENSITY (Air=1) : N/E FREEZING POINT: Not Applicable BOILING POINT: Not Applicable SOLUBILITY IN WATER: Insoluble WATER REACTIVE: No



MATERIAL SAFETY DATA SHEET

REACTIVITY HAZARD DATA

STABILITY: Stable
 CONDITIONS TO AVOID: Open flame, welding arcs, heat.
 INCOMPATIBILITY (MATERIALS TO AVOID): Reactive metals, aluminum, magnesium, strong oxidizing agents.
 HAZARDOUS DECOMPOSITION PRODUCTS: CO2, CO, HCI, small amounts of phosgene and chlorine.
 HAZARDOUS POLYMERIZATION: Will not occur.

TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Limited Qty

REGULATORY INFORMATION

SARA TITLE III (Superfund Amendments and Reauthorization Act):

TRICHLORETHYLENE YES PERCHLOROETHYLENE YES ACETONE NO CARBON DIOXIDE NO

National Refrigerants, Inc. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other methods of use of the product and of the information referred to herein are beyond the control of National Refrigerants. National Refrigerants expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

DATE OF LATEST REVISION/REVIEW: PERSON RESPONSIBLE FOR MSDS: 1/2013 Matt Callahan