

Drying Agent for A/C Systems

NC ONE & DONE A/C DRY is an A/C drying agent formulated with a dehydrating agent which converts harmful moisture in the system to an inert silicone oil. This oil blends with the a/c lubricating fl¬uid to further enhance lubrication inside the A/C system. NC ONE & DONE A/C DRY should be used whenever moisture levels in the system exceed generally accepted industry levels (100ppm for POE or 50ppm for Mineral/AB oils.) Always use NC ONE & DONE A/C DRY at least 20 minutes before introducing any NC ONE & DONE LEAK STOP Product into the system if moisture exceeds, or could exceed these levels. Treats systems up to 5 tons.

FEATURES & BENEFITS

- · Eliminates Moisture in the System
- Quick & Easy Installation
- Compatible With All Refrigerants Excluding Ammonia ... and All Oils

DIRECTIONS:

STEP 1. Turn the a/c system on and verify the unit is running. Connect NC ONE & DONE A/C DRY to the low-side service port of the system. This is generally the large line.

STEP 2. Ensure the valves on manifold gauge set are closed. Start by connecting the high side (red) line of manifold gauge set to the high side service port. Remove NC ONE & DONE A/C DRY from the Mylar bag and loosely connect the middle manifold hose (yellow) to the 1/4" SAE male fitting of the NC ONE & DONE A/C DRY being careful NOT to depress the Schrader core. Quickly open the high side manifold valve to purge air out of the yellow hose. Now close the high side manifold valve, and quickly tighten the yellow hose fitting to the injector.

STEP 3. Next rapidly open and close the high side valve of the manifold gauge allowing a small amount of liquid to flow through the yellow hose and NC ONE & DONE A/C DRY tube. With high side valve of the

manifold gauge set closed, wait one minute for the yellow hose NC ONE & DONE A/C DRY to equalize to suction pressure. Disconnect NC ONE & DONE A/C DRY from suction service port and from manifold gauge set. Allow unit to run for at least 1hour to ensure product has circulated in the system.

Refer to product label & Safety Data Sheet for precautionary and First Aid Information. The SDS is available on the NRP website at www.nrproducts.com

TRAIS
SYSTEMS
UP 5
TO NS
TONS

Eliminates
Moisture in
the System
Easy-to-Use
Installation
Compatible with
All Refrigerants
Except Ammonia