

Air-Acetylene Equipment

FEATHER FLAME ACETYLENE KIT



Economically priced air fuel kit which has a tip design that produces excellent flame characteristics for soldering and light brazing. Contains NHA12 hose, NEA1G regulator, NAA1 handle and NBA4 Kit.

Part No.	Tip	Regulator Fitting
NKA37H	NBA4	"B" Cylinder

TARGET® TORCH ACETYLENE KITS



NKX4B

These kits feature the very hot compact adjustable Target® tips for professional soldering and brazing applications. Kits include quick disconnect handle, UL listed regulator, hose and accessories.

Part No.	Tip	Regulator Fitting
NKX4B	NGA5, NGA14	"B" Cylinder
NKX4BCW*	NGA5, NGA14	"B" Cylinder
NKX5B	NGA5	"B" Cylinder
NKX6MC	NGA3, NGA8	"MC" Cylinder

*Includes a tank stand

J TIPS



NGA3J

- Adjustable and quiet
- Heat resistant
- Fits NGG4 handle
- Air acetylene tip
- Tip includes filter

Part No.	Flame Diameter (In.)	Soft Solder (In.)	Silver Solder (In.)
NGA3J	5/16	3/8 to 1 1/8	1/8 to 1/2
NGA8J	3/8	1 1/8 to 2 5/8	5/8 to 1 1/8

TARGET® TIPS



NGA3

- Very hot turbine flame
- Tips have a filter and removable orifice
- Tips fit NGG-4 handle
- Interchangeable with other quick disconnect style tips
- Unique mixer design cuts brazing time by 30% over conventional tips
- Adjustable tips that do not burn up
- Made of heavy stainless steel and brass

Part No.	Flame Diameter (In.)	Soft Solder (In.)	Silver Solder (In.)
NGA2	1/4	1/8 to 1/2	1/8 to 1/4
NGA3	5/16	3/8 to 1 1/8	1/8 to 1/2
NGA5	5/16	7/8 to 1 5/8	3/8 to 7/8
NGA8	3/8	1 1/8 to 2 5/8	5/8 to 1 1/8
NGA11	7/16	1 5/8 to 3 3/8	7/8 to 1 5/8
NGA14	1/2	2 1/8 to 4 1/8	1 1/8 to 2 1/8
NGA32	3/4	3 1/8 to 6 1/8	1 5/8 to 4 1/8

EZE-LITE® TIPS



NGA3L

- Innovative spark igniting turbine flame tip ignites with the push of a button
- Interchangeable with other quick disconnect tips
- Removable/cleanable orifice
- Fits NGG4 handle

Part No.	Flame Diameter (In.)	Soft Solder (In.)	Silver Solder (In.)
NGA3L	1/4	3/8 to 1 1/8	1/8 to 5/8
NGA5L	5/16	Up to 1 1/2	Up to 3/4
NGA8L	3/8	1 1/8 to 2 5/8	5/8 to 1 5/8
NGA14L	1/2	2 1/8 to 4 1/8	1 1/8 to 2 1/8

ACET-O-LITE® TIPS



NBA3

- Threaded, screw-in
- Quiet, adjustable flame
- Fits NAA1 handle
- Replace Prestolite, Uniweld screw-in tips

Part No.	Flame Diameter (In.)	Soft Solder (In.)
NBA1	1/16	1 1/16 to 1/4
NBA2	1/8	1/4 to 3/8
NBA3	3/16	3/8 to 5/8
NBA4	1/4	5/8 to 1 1/8
NBA5	5/16	1 1/8 to 1 5/8
NBA6	7/16	2 1/8 to 4 1/8

ACET-O-LITE® HANDLE, SCREW-IN



- This handle has the adjustment valve in front for single hand operation
- Needle valve design enables very fine flame adjustments
- This torch will keep your tips burning efficiently in drafts, winds and adverse conditions
- Made with quality brass and durable materials
- Uses standard 3/8-24 LH "A" size hose fittings
- Acet-O-Lite® torch will work with all "NBA" style tips

Part No.	Description
NAA1	Acet-O-Lite® Screw-in Handle

SNAP-IN STYLE HANDLE



- This handle has a quick disconnect to rapidly change tips
- Comfortable grooved handle is made of very durable materials
- Use 3/5-24 LH "A" hose fittings
- The Target® Torch handle will work with all "NGA" style tips

Part No.	Description
NGG4	Target® Torch Snap-In Syle Handle

SNAP ADAPTERS



Adapts the NRP wide variety of threaded pencils, brushes or Target® Tips to torch handles with snap-in design.

Part No.	Description
NBRS665	Thread Tip to Snap-In Handle Adapter
NBRS700	Air/Fuel Screw-In Tips to Acetylene Fuel Handle
NBRS770	Snap-In Tip to Screw-In Handles

CYLINDER ADAPTERS



NBRS364



NBRS365

Part No.	Description
NBRS364	"MC" Cylinder to "B" Regulator
NBRS365	"B" Cylinder to "MC" Regulator

ACETYLENE REGULATORS



NEA1G

- UL Listed regulators, manufactured of solid brass, are made for rugged use.
- Specially designed conical seat and neoprene diaphragm
- The inlets have filters to prevent dirt from entering the regulator
- "A" hose fitting 3/8-24 LH

Part No.	Description	Contents (PSI)
NEA1G	Single Gauge Acetylene Regulator for B Tank	0 to Full
NEA2G	Single Gauge Acetylene Regulator for MC Tank	0 to Full

ACETYLENE HOSES



- Constructed from quality 3/16" ID single ply, fabric reinforced grade "R" hose
- 200 PSI working pressure
- 3/8-24 "A" fittings

Part No.	Description
NHA36	Hose, 6' Long
NHA312	Hose, 12' Long
NHA325	Hose, 25' Long

ACETYLENE STANDS



NC850CW

- Heavy duty steel with hose rack, support base and handle
- Ideal stand for air-acetylene kits

Part No.	Description
NC800	Fits "MC" Cylinder
NC850	Fits "B" Cylinder
NC850CW	Fits "B" Cylinder, with wheels

WELDING AND BRAZING KITS



NKA125B

Kits are prematched to different tank sizes. Portable carts and carrying stands are available.

Each kit includes :

- Welding handle
- 12' hose
- Dual gauge O₂ regulator.
- Dual gauge "MC or B" regulator
- #1 & #3 welding tips
- Goggles, Lighter

Part No.	Description
NKA125M	For "MC" Tank
NKA125M12P	For "MC" Tank, w/ Plastic stand
NKA125B	For "B" Tank

FRONT VALVE/WELDING AND BRAZING KITS, STUBBY™ STYLE



NKA700M

Stubby™ style products are rugged and designed for commercial applications where size is a consideration. These tips give the user close up control and they maximize movement in tight areas. Various other tips are available. The torch is compact and durable.

Each kit includes:

- Welding handle
- #1 & #3 Stubby™ style welding tips
- 12' hose
- Dual gauge "MC" regulator
- Dual gauge O₂ regulator
- NKA725M12P includes a standard long tip
- Goggles, Lighter

Part No.	Description
NKA700M	Stubby™ Kit for MC Tank
NKA700M12P	Stubby™ Kit for MC Tank with Plastic Cart
NKA725M12P	Stubby™ Kit for MC Tank with Plastic Stand

WELDING AND BRAZING TORCH



Part No.	Description
NTW10A	Welding Torch with "A" Hose Fittings and Rear Valve Design

WELDING AND BRAZING TORCH, STUBBY™ STYLE



- Use with Stubby™ style 2033 or standard style 3033 tips

Part No.	Description
NTW5A	Compact Brazing Torch with "A" Hose Fitting and Front Needle Valve

CUTTING ATTACHMENT



Part No.	Description
NTCA10CAT	Cutting Attachment with 2320 #1 Tip

REPLACEMENT CUTTING TIPS




N23201

Part No.	Description
N23200	Replacement Cutting Tip, Small #0
N23201	Replacement Cutting Tip, Medium #1
N23202	Replacement Cutting Tip, Large #2

Oxy-Fuel Equipment

REPLACEMENT WELDING/BRAZING & HEATING TIPS




Fits all NRP oxy-fuel handles

Part No.	Description	Brazing Capacity (OD In.)
N30331	Welding Tip, #1	1/4 to 1 1/8
N30333	Welding Tip, #3	1/2 to 1 3/8
N3033H15	Heating Tip, #15	to 1 5/8
N3033H30	Heating Tip, #30	to 3 1/8

Fits Prestolite® oxy-fuel handles

Part No.	Description	Brazing Capacity (OD In.)
N325015	W200 Heating Tip, #15	to 1 5/8
N325030	W200 Heating Tip, #30	to 3 1/8

WELDING & BRAZING TIPS, STUBBY™ STYLE



- Fits all NRP oxy-fuel handles
- Rugged design for commercial applications
- Short heavy duty design
- Gives up close control and maximizes movement in tight areas
- Made of brass and copper

Part No.	Description	Tip#	Brazing Capacity (OD In.)
N20330		0	3/16 to 3/4
N20331	Welding and	1	5/16 to 1 1/8
N20332	Brazing Tip	2	3/16 to 3/4
N20333		3	5/8 to 1 3/8
N2033H15	Heating Tip	15	to 1 5/8
N2066T00		00	to 5/8
N2066T0	Twin Tip	0	to 1 1/8
N2066T1		1	to 2 1/8
N2077G00		00	to 5/8
N2077G0		0	to 1 1/8
N2077G1	G Brazing Tip	1	to 1 5/8
N2077G2		2	to 2 1/8
N2077G3		3	to 3 1/8
N2011F6	Flex Tip, 6" Long	—	to 1 5/8
N2011F10	Flex Tip, 10 Long	—	to 1 5/8

OXY-FUEL REGULATORS



NE025A

These UL listed regulators are manufactured from durable brass with a neoprene rubber diaphragm, inlet filters and conical seat design. NRP regulators give the constant and accurate gas flow that is needed by professionals.

Part No.	Description	Contents (PSI)	Delivery (PSI)
NEA25MA	Dual Gauge Acetylene Regulator for MC Tank	0 to 400	0 to 30
NEA25BA	Dual Gauge Acetylene Regulator for B Tank	0 to 400	0 to 30
NE025A	Dual Gauge Oxygen Regulator	0 to 4000	0 to 100

NITROGEN REGULATOR



- Heavy duty regulator delivers pressure and volume most requested by professionals
- Forged brass body

Part No.	Description	Contents (PSI)	Delivery (PSI)
NEN450F	Nitrogen Regulator, 1/4" MFL outlet fitting	0 to 4000	5-450

DUAL OXY-ACETYLENE HOSES



NSW12A

- Constructed from quality 3/16" ID single ply, fabric reinforced grade "R" hose
- 200 PSI working pressure
- 3/8-24 "A" fittings

Part No.	Description
NSW12A	Dual Hose Kit, 12' Long
NSW25A	Dual Hose Kit, 25' Long

MAPP/PROPANE SWIVEL TORCHES



NPG360L

- Hot turbine flame
- Used with either propane or MAPP® gas
- 360 degree tip rotates to any position
- Heavy duty brass regulator
- Stainless steel tip ends

Part No.	Description
NGP360L	Mapp/Propane Torch, Self Igniting, Push Button
NGP360R	Mapp/Propane Torch, Match Lit, for Disposable Cylinders
NGP360J	Mapp/Propane Torch with J Tip

INSTANT IGNITION TRIGGER TORCH



- Hot turbine flame
- Flame adjustment valve
- Use Mapp® or propane fuel

Part No.	Description
NGP600	Mapp/Propane Torch, Trigger Light

BLOW GUN



- OSHA approved nozzle
- Durable construction
- ON/OFF lever
- 1/4" male flare inlet, 1/8" FPT outlet

Part No.	Description
NBG1	Quality Die Cast Blow Gun

REFRIGERANT HOSE



- Nylon lined, low porosity
- UL approved
- Suitable for R12, R134a, R22, R500, R404A, R410A and HCFC blends

Part No.	Description
NH72Y	6' Refrigerant Hose

NITROGEN PURGE & BLOW GUN KITS



NKPN1

Heavy duty high pressure regulator and hose

- 6' Hose
- Quality die-cast blow gun
- EN-460F high pressure regulator
- Multiple uses: purges, blow, leak tests

Part No.	Description
NKPN1	Nitrogen Purge and Blow Gun Kit
NKPN20S	Nitrogen Purge and Blow Gun Kit with Stand for 20 Cubic Ft. Cylinders
NKPN40S	Nitrogen Purge and Blow Gun Kit with Stand for 40 Cubic Ft. Cylinders

SINGLE FLINT LIGHTERS



N3011



N3011X

Part No.	Description
N3011	Single Flint Lighter (Flint Included)
N3011X	Renewal Flints (5 each)

Oxy-Fuel Equipment

CYLINDER WRENCH



Part No.	Description
NMA2	Cylinder Wrench

REPLACEMENT GAUGES



NSTE331

Quality gauges for the NRP air acetylene, oxygen, fuel and nitrogen regulators

Part No.	Application	Diameter (In.)	Scale
NMA8016F	Flat Gauge, NEA1G	1 1/2	0 to Full
NSTE331	Delivery, NEA25	2	0 to 30#
NSTE332	Contents, NEA25	2	0 to 400#
NSTE357	Delivery, NEO25	2	0 to 100#
NSTE334	Contents, NEO25	2	0 to 4000#
NSTE391	Delivery, NEN450F	2	0 to 1000#
NSTE392	Contents, NEN450F	2	0 to 4000#

FLAME GUARD



Protects wood, painted or metal surfaces from the heat and flame of a torch.

Designed for soldering and brazing using propane and MAPP gas.


Part No.	Description
NFG	9" x 12"

HALIDE LEAK DETECTOR



NGP18R

Cylinder NOT included



NDA8A

Leak detector for use with disposable propane or MAPP® gas cylinders.

The flame, when adjusted to heat the reactor plate, quickly changes color as the search hose passes a refrigerant leak.

Part No.	Description
NGP18R	Halide Leak Detector
NDA8A	Replacement Reactor Plate

OXY-FUEL CYLINDER STAND & CART



NC1300



NC1200P

Part No.	Description
NC1200P	Plastic Carry Stand, "R" Oxy, "MC"
NC1300	Steel Wheeled Cart, "Q" Oxy, "B"

ADAPTERS, TORCH/REGULATOR TO HOSE



NBRS341

Part No.	Description
NBRS341	"A" LHF to "B" LHM
NBRS342	"A" RHF to "B" RHM