



GLOBESAVER™







- Dual intake connections
- Two stage design: second stage starts pump at a lower pressure to pull a deeper ultimate vacuum
- Ergonomic sure-grip handle
- High vacuum rating
- Gas ballast feature: helps keep the pump oil clean by reducing condensation of moisture

Vacuum Pump	GVP3	GVP6	GVP12
Free Air Displacement (CFM)	3	6	12
Stages	2 stage rotary vanes	2 stage rotary vanes	2 stage rotary vanes
Field Blankoff	15 microns	15 microns	15 microns
Intake Male Flare (In.)	1/4 MFL x 3/8 MFL	1/4 MFL × 3/8 MFL	3/8 MFL x 1/2 MFL
Horsepower	1/4	1/2	1/2
RPM	1720 @ 60 Hz	1440 @ 50 Hz, 1730 @ 60 Hz	1440 @ 50 Hz, 1730 @ 60 Hz
Voltage	115	115/220	115/220
Oil Capacity	14.0 Oz.	34 Oz.	34 Oz.
Length (In.)	14	16.93	18.89
Width (In.)	5.71	5.71	5.71
Height (In.)	10.5	10.43	11.81
Unit Weight (Lbs.)	23	31	39
Shipping Weight (Lbs.)	27	38	49









Vacuum Pump	TEZ8	
Free Air Displacement (CFM)	8	
Field Blankoff	<20 Microns	
Intake Male Flare (In.)	1/4, 3/8, 1/2	
Horsepower	1/2	
Power	115 VAC, 60 Hz, 10 Amps	
Oil Capacity	34 Oz.	
Length (In.)	14.25	
Width (In.)	9.4	
Height (In.)	10.3	
Unit Weight (Lbs.)	28	

ΙΕΖΟ

- Three intake connections
- 5-second oil change[™]
- High speed turbine fan keeps pump and oil cool
- Exhaust system vents moisture remotely (standard garden hose connection) without breaking vacuum
- Wide, low stance prevents accidental tipping
- TEZOM cartridges are available in the following quantities:

Part No.	Description
TZM1PK	TEZ8 Oil Cartridge (1 Cartridge)
ТΖМЗРК	TEZ8 Oil Cartridge (3 Cartridges/Pack)
TZMCRT	TEZ8 Oil Cartridge (24 Cartridges/Carton)

