

# VR5



## Commercial Refrigerant Recovery Unit

The VR5 is designed for commercial installations. It consists of a belt-driven open-type compressor, which will recover systems into a vacuum. The VR5 has been designed to be simple to operate and service. The unit is mobile with all components mounted on a sturdy steel frame. It utilizes a rugged open compressor which eliminates all problems related to the handling of contaminated refrigerant. Any recovery cylinder with two valves can be used.



Recovery Equipment

### Specifications

Power: 1.5 HP, 20 Amps, 230 Volt, 60 Hz, 1PH  
Unit Weight: 195 Lbs  
Dimensions: 24" L x 22" W x 45" H  
Connections: 1/2" MFL Inlet, 1/2" MFL Outlet

### For use with:

Group III R12, R134a, R406A, R500  
Group IV R401A, R409A, R417C, R401B, R419B, R411A, R407D, R22, R411B, R422E, R502, R427A, R408A, R407C, R402B  
Group V R407A, R404A, R402A, R507, R407B, R410B, R410A

### Applications

- Large field erected systems with long piping runs
- System requiring large vapor capacity
- Supermarkets
- Salvage yards
- Large Industrial/Commercial

Refrigerant Groups	Push/Pull Liquid Refrigerant	Vapor Refrigerant	Shut-Off Vacuum
III	63.0 lbs./min	1.84 lbs./min	20"
IV	61.75 lbs./min	1.92 lbs./min	15"
V	31.8 lbs./min	1.42 lbs./min	13.5"

