

RECOVERY EQUIPMENT QUICK REFERENCE CHART

Unit Part Number	AVAILABLE FEATURES											AVAILABLE POWER				For use with Refrigerants per the ARI 740-98 Categories								
	Liquid Direct	Oil Less	Hermetic	Cylinder Shut-Off	Pump-Out	Subcool	UL Listed	Hoses	Sight Glass	Cylinder	EPA + ARI Certified	115 Volt	220 Volt	230 Volt	460 Volt	1 Phase	3 Phase	Pneumatic	I	II	III	IV	V	VI
Recovery Units																								
G1SINGLE	•	•								•	•	•		•							•	•	•	
G5TWIN	•	•								•	•	•		•							•	•	•	
GS3700	•	•			•					•	•	•		•							•	•	•	
GS3710	•	•		•	•					•	•	•		•							•	•	•	
LV2000			•		•					•	•	•		•							•	•	•	
LV2001			•	•	•				•	•	•		•		•						•	•	•	
AR1UL		•		•		•	•		•	•	•		•		•						•	•		
REVAC		•		•					•	•	•		•		•						•	•		
REVAC-UL		•		•	•		•	•	•	•	•		•		•						•	•		
RAD700							•			•	•			•							•	•		•
RLV700			•	•	•		•	•	•	•	•			•							•	•	•	
LV20	•	•			•					•								•			•	•	•	
LV5			•	•	•					•		•	•		•						•	•	•	
LV8	•	•			•					•	•	•	•	•	•	•		•		•	•	•		
VR11			•	•	•					•	•	•	•		•				•					
VR13		•								•								•						•
TS4		•			•					•			•		•						•	•		
Liquid Pumps																		For use with the following Refrigerants						
LP11	•									•														R11, R113
LP12	•									•														R12
LP13	•	•							•								•							R13, R23, R508A, R503, R508B
LP22	•									•		•		•										R11, R12, R22, R113, R123, R500, R502, R134a & Blends
LPO	•									•		•												Transfer refrigeration oil

* ARI STANDARD 740-98

Category I: low pressure, R113, R123, R11

Category II: medium pressure - low moisture, R114

Category III: medium pressure, R12, R134a, R401C, R406A, R5

Category IV: medium high pressure, R401A, R409A, R401B, R412A, R411A, R407D, R22, R411B, R502, R407C, R402B, R408A, R50

Category V: high pressure, R407A, R404A, R402A, R507, R407B, R410A

Category VI: very high pressure - high moisture, R13, R23, R508A, R503, R508B